



FE87 full range driver

FEATURES

- Aluminum cone
- 25mm voice coil
- extended frequency response
- low distortion
- Shielded

| Specifications | | Magnet System | |
|------------------------|----------------|----------------------|----------------------|
| Overall Dimensions | 79X79X52.7mm | Magnet system type | ferrite,shield |
| Net. Weight | 0.56 kgs | Magnetic Gap Height | 3mm |
| Nominal Power Handling | 13 W rms | B Flux Density | 1.03T |
| Nominal Impedance | 8 Ohms | Bl Product | 3.1Tm |
| Sensitivity 1W/1M | 84dB | Max Linear Excursion | 1mm +/- |
| Frequency Response | 100-25,000Hz | T/S Parameter | |
| Resonant frequency | 101Hz | Cms | 1.181mm/N |
| Voice Coil | | Sd | 27.34cm ² |
| Voice Coil Diameter | 25mm | Vas | 1.254L |
| Voice Coil Height | 5mm | Mmd | 1.991gm |
| Voice Coil Former | Black aluminum | Mms | 2.073gm |
| Voice Coil Wire | copper round | Qms | 3.381 |
| Number of Layers | 2 | Qes | 0.939 |
| DC Resistance | 6.776 Ohms | Qts | 0.735 |

SPL vs Freq

