


JRC-23F



12.5×7.5×10

UL E158859

Features	
<ul style="list-style-type: none"> • Low coil power consumption. • High sensitivity. • Small size, light weight. • PC board mounting. • Suitable for automation facilities, telecommunication equipment, wireless radio remote control, sound control toys application etc. 	

Ordering Information	
JRC-23F <u>H</u> <u>S</u> <u>1</u> <u>DC12V</u> 1 2 3 4 5	
1 Part number: JRC-23F	3 Enclosure: S: Sealed type; NIL: Dust cover
2 Coil power consumption: NIL:0.2W; H:0.15W	4 Contact rating: 0.5:0.5A/125VAC; 1:1A/30VDC
	5 Coil rated voltage(V): DC:1.5,3,5,6,9,12,24

Contact Data			
Contact Arrangement	1C (SPDT(B-M))		
Contact Material	Ag (Au clad) AgNi (Au clad)		
Contact Rating (resistive)	0.5A/125VAC, 1A/30VDC, 0.3A/60VDC		
Max. Switching Power	30W 62.5VA		
Max. Switching Voltage	60VDC 125VAC	Max. Switching Current: 1A	
Contact Resistance or Voltage drop	≤100mΩ	item 4.12 of IEC 61810-7	
Operational life	Electrical	10 ⁵	item 4.30 of IEC 61810-7
	Mechanical	5×10 ⁶	item 4.31 of IEC 61810-7

Coil Parameter								
Dash numbers	Coil voltage VDC		Coil resistance Ω ±10%	Pickup voltage VDC(max) (80% of rated voltage)	Release voltage VDC(min) (10% of rated voltage)	Coil power consumption W	Operate Time ms	Release Time ms
	Rated	Max.						
001-150	1.5	3.0	15.0	1.2	0.15	0.15	<5	<5
003-150	3	6.0	60.0	2.4	0.30			
005-150	5	10.0	166.7	4.0	0.50			
006-150	6	12.0	240.0	4.8	0.60			
009-150	9	18.0	540.0	7.2	0.90			
012-150	12	24.0	960.0	9.6	1.20			
024-150	24	48.0	3840.0	19.2	2.40			
001-200	1.5	2.25	11.3	1.2	0.15	0.2	<5	<5
003-200	3	4.5	45.0	2.4	0.30			
005-200	5	7.5	125.0	4.0	0.50			
006-200	6	9.0	180.0	4.8	0.60			
009-200	9	13.5	405.0	7.2	0.90			
012-200	12	18.0	720.0	9.6	1.20			
024-200	24	36.0	2880.0	19.2	2.40			

CAUTION: 1.The use of any coil voltage less than the rated coil voltage will compromise the operation of the relay.
 2.Pickup and release voltage are for test purposes only and are not to be used as design criteria.
 3.Unless otherwise stated, the rated coil voltage specified in coil parameter table shall be used for all tests and its application to the relay.

Operation condition		
Insulation Resistance	1000MΩ min (at 250V 500V)	Item 7 of IEC 61810-5
Dielectric Strength	Between contacts	Item 6 of IEC 61810-5
	Between contact and coil	Item 6 of IEC 61810-5
Shock resistance	100m/s ² 11ms	IEC68-2-27 Test Ea
Vibration resistance	10~55Hz double amplitude 3.3mm	IEC68-2-6 Test Fc
Terminals strength	5N	IEC68-2-21 Test Ua1
Solderability	235℃ ± 2℃ 3 ± 0.5s	IEC68-2-20 Test Ta method 1
Ambient Temperature	-30~70℃	
Relative Humidity	35%~85% (at 40℃)	IEC68-2-3Test Ca
Mass	2.2 g	

Safety approvals	
Safety approval	UL&CUR
Load	1A/30VDC 0.5A/125VAC 0.3A/60VDC

Dimensions		mm/inch
<p>NOTES 1).Dimensions are in millimeters. 2).Inch equivalents are given for general information only.</p>		