



| | | | | | |
|-----|--------------------|----------|---------|------|---------------------|
| 8 | HEAT SHRINK TUBING | | | 1 | HT-56/5X193 |
| 7 | FERRULE | NOTE 6 | NOTE 2 | 1 | FR-39/32X95 |
| 6 | CONTACT PIN | NOTE 1 | NOTE 4 | 1 | SMA1111A2-6-092/06 |
| 5 | GASKET | SILICONE | RED | 1 | GS-6/43X06 |
| 4 | RETAINER RING | NOTE 3 | NATURAL | 1 | SMA5000-4-B |
| 3 | INSULATOR | NOTE 5 | NATURAL | 1 | SMA1111A2-3T-50-B |
| 2 | BODY | NOTE 1 | NOTE 2 | 1 | SMA1111A2-2-27/17-A |
| 1 | SHELL | NOTE 1 | NOTE 2 | 1 | SMA5000-1-C |
| NO. | DESCRIPTION | MATERIAL | FINISH | Q'TY | DRAWING NO. |

| | | | | | |
|---------------------------------------|--|--|--|--------------------------------|-----------|
| DIMENSIONS ARE IN MILLIMETERS | | | | PART NO. SMA1111A2-3GT50G-5-50 | |
| UNLESS OTHERWISE SPECIFIED TOLERANCES | | | | APPROVED | DATE |
| 0.5-6 = ±0.2 | | | | | 10-11-01' |
| 6-30 = ±0.4 | | | | CHECKED | DATE |
| 30-120 = ±0.6 | | | | | 10-11-01' |
| 120-315 = ±1 | | | | DRAWN | DATE |
| 315-1000 = ±1.6 | | | | | 10-11-01' |
| 1000-2000 = ±2.4 | | | | FILE NO. | |

| | |
|---|--|
| Amphenol | |
| TITLE SMA CRIMP PLUG (RG-174/U,188A/U,316/U) | |
| DRAWING NO. KJ-SMA1111A2-3GT50G-316U-50 | |
| ITEM NO. | |