

MILAN S.r.l. a socio unico

**Head Office – Export department:**  
 Viale Europa, 74  
 20090 Cusago (MI) Italy  
 T. +39 02 9039.4556-4158  
 F. +39 02 9039.4551  
 www.taskercables.com

**Ufficio Commerciale e Centro Distribuzione**  
 Viale Europa 72 Strada F12  
 20090 Cusago (MI) Italy  
 T. +39 02 9039.0037-0059  
 F. +39 02 9039.0049  
 www.tasker.it



## Technical Datasheet

# tasker® C202 Balanced Microphone Cable



**CATEGORY** Balanced Microphone Cable (See Audio Catalogue)  
**APPLICATIONS** Premade Cables and Small Microphones

- A:** Black Soft **PVC** Sheath. Outer cable Diam. Ø: 3,00 (±0,10) mm.
- B:** Shielding in O.F.C. tinned copper spiral covering 100%.
- C:** Core Insulation with PVC, colored one Red and one White. Diam. Ø: 0,90 (±0,10) mm.
- D:** O.F.C. tinned copper formation 12x0,10 mm. Nom. Cross section 2x0,08 mm<sup>2</sup>.

**MARKING** tasker® C 202 2x0,08 mm<sup>2</sup> O.F.C. Balanced Mini Microphone Cable  
**CUSTOM** This product is also available in **L.S.Z.H., PE, PUR**, with or without **Steel Armor**.

### Cable Properties

<b>Conductor Resistance</b>	203 Ω/Km
<b>Capacity Core/Core</b>	170 pF/mt
<b>Capacity Core/Shield</b>	310 pF/mt
<b>Max Rated Voltage</b>	49 V
<b>Operative Temperature</b>	-15/+70°C

<b>USE</b>	<b>X</b>	Indoor	Interno Edificio	<b>INSTALLATION</b>	<b>X</b>	Fixed	Fissa	<b>INFORMATION</b>	<b>X</b>	RoHS2 Compliant
<b>Impiego</b>	<b>X</b>	Outdoor Limited	Esterno Limitato	<b>Posa</b>	<b>X</b>	Restricted Mobile	Mobile Limitata	<b>Informazioni</b>	<b>X</b>	Ver. A / 16.05.16
		Outdoor	Esterno			Mobile	Mobile			
		Outdoor Direct Burial	Esterno Interrato			Mobile in Drag Chain	Mobile in Catena			