



REVISION RECORD

REV	ECN	DESCRIPTION	DRFT	DATE
-----	-----	-------------	------	------



NOTES:

- Rated voltage/current : 3pin A: 250V / 4A
4pin A: 250V / 4A
5pin A: 60V / 4A
6pin A: 30V / 2A
8pin A: 30V / 2A
5pin B: 60V / 4A
4pin D: 250V / 4A

- Withstanding voltage : 3,4pin A: AC1500V/1Min
5pin A: AC1120V/1Min
6,8pin A: AC500V/1Min
5pin B: AC1120V/1Min
4pin D: AC1500V/1Min

3.Levels of protection: IP67

4.Wire range :

- 3pin A: 24~20AWG/0.25~0.52mm²
- 4pin A: 24~20AWG/0.25~0.52mm²
- 5pin A: 24~20AWG/0.25~0.52mm²
- 6pin A: 24~22AWG/0.25~0.34mm²
- 8pin A: 24~22AWG/0.25~0.34mm²
- 5pin B: 24~20AWG/0.25~0.52mm²
- 4pin D: 24~20AWG/0.25~0.52mm²

5.Cable OD: 4~8mm

6.Wire connection mode: screw

7.Operating temperature: -25°C~+105°C

8.RoHS Compliance

5pin B Coding	4pin D Coding
Pin Assignments Front View	Pin Assignments Front View

PB-M12X-XXP-MM-SL7001-00A(H)
Coding: A,B,D
Pin number: 03,04,05, 06,08

3pin A Coding	4pin A Coding	5pin A Coding	6pin A Coding	8pin A Coding
Pin Assignments Front View	Pin Assignments Front View	Pin Assignments Front View	Pin Assignments Front View	Pin Assignments Front View

DETACHED LISTS	PART NO.: PBM12XXXPMMSL700100AH	宁波高松电子有限公司 NINGBO DEGSON ELECTRICAL CO., LTD		
	APPD:	NAME: PB-M12X-XXP-MM-SL7001-00A(H)		
	CHKD:	DRAWING NO.: XXXXXXXX-XX-CXX		
	DRFT: LZ 2018.10.08	TITLE: CUSTOMER DRAWING	REV: D0-1	SHEET: 1/1
THIRD ANGLE PROJECTION		MM (INCH)	DO NOT SCALE DRAWING	SCALE: 1:1