

MILAN S.r.l. a socio unico

Head Office – Export department:
 Viale Europa, 74
 20090 Cusago (MI) Italy
 T. +39 02 9039.4556-4158
 F. +39 02 9039.4551
 www.taskercables.com

Ufficio Commerciale e Centro Distribuzione
 Viale Europa 72 Strada F12
 20090 Cusago (MI) Italy
 T. +39 02 9039.0037-0059
 F. +39 02 9039.0049
 www.tasker.it

Technical Datasheet

tasker® C140 – 1x0,75 mm²

Special Coaxial Cable 75 Ω



A	B	C	D	E
---	---	---	---	---

CATEGORY Coaxial cable 75 Ω (See Video Catalogue)
APPLICATIONS Digital Audio Transmission according to AES/EBU Standards

- A:** Dark Blue **L.S.Z.H.** sheath. Outer Diam. Ø 8,00 (±0,20) mm.
- B:** First Shielding O.F.C. red copper Braid covering 90%.
- C:** Second Shielding in Aluminum foil tape, covering 100 %.
- D:** Core Insulation in PEE. Diam. Ø 4,90 (±0,20) mm.
- E:** Stranded Formation 80x0,11 mm in O.F.C. Red Copper.
Nom. Cross section 1x0,75 mm².

MARKING tasker® C140 1x0,75 mm² (75 W) O.F.C. Double Shield Coaxial Digital Audio-Video Cable
CUSTOM PRODUCTION This product may be custom produced also in **LSZH, PE, PUR**, with or without Metallic Armor.

Cable Properties

Conductor Resistance	21,93 Ω/Km
Capacity Core/Shield	66 pF/m.
Velocity of Propagation	66%
Impedance	75 Ω
Max Rated Voltage	49V
Operative Temperature	-15/+70°C

Attenuation dB/100 m.

50 MHz	7,50
100 MHz	11,50
200 MHz	16,50
400 MHz	23,50
800 MHz	33,50
1000 MHz	38,00

USE	<input checked="" type="checkbox"/>	Indoor	Interno Edificio	INSTALLATION	<input checked="" type="checkbox"/>	Fixed	Fissa	INFORMATION	<input checked="" type="checkbox"/>	RoHS2 Compliant
Impiego		Outdoor Limited	Esterno Limitato	Posa	<input checked="" type="checkbox"/>	Flexible Limited	Flessibilità limitata	Informazioni	<input checked="" type="checkbox"/>	Ver. A / 27.06.16
		Outdoor	Esterno			Dynamic (Drag Chain)	Mobile in Catena			
		Outdoor Direct Burial	Esterno Interrato			Dynamic (Torsion)	Mobile in Torsione			